



PGGU2.MH17767
Marking and Labeling System Materials - Component

Page Bottom

Marking and Labeling System Materials - Component

See General Information for Marking and Labeling System Materials - Component

METALPHOTO, DIV OF HORIZONS INCORPORATED

MH17767

18531 S MILES RD
 CLEVELAND, OH 44128 USA

Face stocks with pressure-sensitive laminating adhesives:

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Metalphoto, Fotofoil M (a)						
	None investigated	150	-40	X	X	O, G

G - Occasional exposure to Gasoline splashing.

O - Occasional exposure to Lubricating Oil.

(a) - Requires further investigation for application surfaces and adhesive

Marking: Company name and model designation.

Last Updated on 2009-11-02

[Questions?](#)[Print this page](#)[Notice of Disclaimer](#)[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





**PGGU2.GuideInfo
Marking and Labeling System Materials - Component**

[View Listings](#)

[Page Bottom](#)

[Marking and Labeling Systems - Component] Marking and Labeling System Materials - Component

[See General Information for Marking and Labeling Systems - Component](#)

The materials covered under this category are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN EQUIPMENT SUBMITTED TO UNDERWRITERS LABORATORIES INC.

USE

This category covers materials intended for use by label printers (converters) in fabricating finished printed adhesive-attached labels intended to provide warnings, instructions and other information subject to permanence of marking requirements. Printed labels employing these materials require examination of printing and other features not evaluated in the investigation of the materials alone.

CONDITIONS OF ACCEPTABILITY

Unless specified otherwise in the individual Recognitions, consideration is to be given to the following Conditions of Acceptability when these components are employed in the end-use equipment:

1. These materials are intended for use indoors, where exposure to high humidity or only occasional exposure to water can be expected. Materials suitable only for indoor dry location use or for additional exposure conditions, such as outdoor use, gasoline splashing, etc., are identified in the individual Recognitions. Materials for which no minimum temperature rating is indicated are considered suitable for use in ambient temperatures down to 0°C (32°F).
2. These materials are suitable for application to smooth, flat surfaces subjected to the temperatures and conditions indicated. Painted surfaces are on metal substrates. Materials indicated as suitable for application to alkyd paint are also considered suitable for application to alkyd paint modified with an amine resin. Materials indicated as suitable for application to a generic plastic are also considered suitable for application to filled or reinforced plastic of the same generic type. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend. Label materials indicated as suitable for use on a metal surface, such as aluminum, are considered suitable for application to alloys of that metal, such as aluminum/magnesium alloys. Label materials indicated as suitable for use on a textured surface may be subject to further investigation to determine suitability for use on a particular textured end-product surface.
3. Materials found suitable for additional printing by the user are identified in the individual Recognitions. Only unprinted (blank) areas of the label are suitable for additional printing. The materials have not been investigated for additional printing using hand implements, such as pen or pencil.
4. The materials have not been investigated for nontransferability or for electrical or flammability properties.
5. The label materials are intended to be applied with sufficient pressure to provide uniform and complete contact with the surface. Heat-activated adhesives shall be activated in accordance with the supplier's instructions regarding temperature, pressure and dwell time. Solvent-activated adhesives shall be activated in accordance with the procedure and solvent recommended by the supplier.

Additional Conditions of Acceptability may be found in the Recognition Report available from the manufacturer.

REQUIREMENTS

The basic standard used to investigate products in this category is [ANSI/UL 969](#), "Marking and Labeling Systems."

UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. UL shall not incur any obligation or liability for any loss, expense or damages, including incidental or consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Guide Information.

Last Updated on 2009-11-05

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.





PGDQ2.GuideInfo Marking and Labeling Systems - Component

[View Listings](#)
[Page Bottom](#)

Marking and Labeling Systems - Component

The products covered under this category are incomplete in certain constructional features or restricted in performance capabilities and are intended for use as components of complete equipment submitted for investigation rather than for direct separate installation in the field. THE FINAL ACCEPTANCE OF THE COMPONENT IS DEPENDENT UPON ITS INSTALLATION AND USE IN EQUIPMENT SUBMITTED TO UNDERWRITERS LABORATORIES INC.

USE

This category covers finished printed adhesive-attached labels suitable for the surfaces and use conditions indicated in the individual Recognitions. The labels are intended to provide warnings, instructions and other information subject to permanence of marking requirements.

CONDITIONS OF ACCEPTABILITY

Unless specified otherwise in the individual Recognitions, consideration is to be given to the following Conditions of Acceptability when these components are employed in the end-use equipment:

1. These materials are intended for use indoors, where exposure to high humidity or only occasional exposure to water can be expected. Materials suitable only for indoor dry location use or for additional exposure conditions, such as outdoor use, gasoline splashing, etc., are identified in the individual Recognitions. Labels for which no minimum temperature rating is indicated are considered suitable for use in ambient temperatures down to 0°C (32°F).
2. The labels are suitable for application to smooth, flat surfaces subjected to the temperatures and conditions indicated. Painted surfaces are on metal substrates. Labels indicated as suitable for application to alkyd paint are also considered suitable for application to alkyd paint modified with an amine resin. Labels indicated as suitable for application to a generic plastic surface are also considered suitable for application to filled or reinforced plastic of the same generic type. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend. Labels indicated as suitable for use on a metal surface, such as aluminum, are considered suitable for application to alloys of that metal, such as aluminum/magnesium alloys. Labels indicated as suitable for use on a textured surface may be subject to further investigation to determine suitability for use on a particular textured end-product surface.
3. The labels have not been investigated for additional printing using hand implements, such as pen or pencil.
4. The labels have not been investigated for nontransferability or for electrical or flammability properties.
5. Labels that have additionally been investigated for use on specific end products are so indicated in the individual Recognitions.
6. The labels are intended to be applied with sufficient pressure to provide uniform and complete contact with the surface. Heat-activated adhesives shall be activated in accordance with the supplier's instructions regarding temperature, pressure and dwell time. Solvent-activated adhesives shall be activated in accordance with the procedure and solvent recommended by the supplier.

Additional Conditions of Acceptability may be included in the Report available from the manufacturer.

REQUIREMENTS

The basic standard used to investigate products in this category is [ANSI/UL 969](#), "Marking and Labeling Systems."

UL, in performing its functions in accordance with its objectives, does not assume or undertake to discharge any responsibility of the manufacturer or any other party. UL shall not incur any obligation or liability for any loss, expense or damages, including incidental or consequential damages, arising out of or in connection with the use, interpretation of, or reliance upon this Guide Information.

[Last Updated](#) on 2010-03-18

[Questions?](#)
[Print this page](#)
[Notice of Disclaimer](#)
[Page Top](#)

Copyright © 2011 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.



Marking and Labeling Systems

UL 969

1 Scope

1.1 These requirements cover adhesive attached labels for use as nameplates or markers; bearing information, instructions, or identification. An adhesive for a label may be pressure sensitive, heat activated, or solvent activated. These labels are intended to be used by manufacturers for application to their products at their place of manufacture.

1.2 These requirements also cover unprinted materials, such as face stocks, label stocks, overlaminations, laminating adhesives, and inks used by label printers to produce labels.

1.3 These requirements apply to marking and labeling systems used on complete devices, appliances, or equipment. The acceptability of a system in a particular application is to be judged under the applicable requirements in the standard covering the device, appliance, or equipment on which the system is used.

1.4 Marking and labeling systems are evaluated for application to specific surface materials that are essentially smooth and flat unless another surface configuration is specified by the manufacturer.

UL 969 does not reference any other UL Standards.

[Table of Contents](#) for UL 969.

[Purchase UL Standards](#)

[UL Standards InfoNet](#)

[UL Standards Catalog](#)